

LH200 The ultimate portable business projector



- Bright 1080p LED projector 2000 LED Brightness
- Truly portable Built-in battery
- Easy to setup Auto keystone and four corner adjustment
- Optional wireless presentations

The LH200 is the brightest 1080p LED projector with built in battery. Designed as the ideal business tool for presentations on the go it features USB display from a mobile device, Bluetooth, HV keystone and four corner adjustment. You can also give wireless presentations from a mobile device using the free HDCast Pro app and optional wireless USB adapter.

Specifications

Display/image		
Display technology	DLP	
Resolution	1080p Full HD (1920x1080)	@
Brightness (LED)	2,000 lumens	
Contrast ratio	200,000:1	
Native aspect ratio	16:9	(< (ok >)
Aspect ratio - compatible	4:3,16:9	
Keystone correction - horizontal	20	
Keystone correction - vertical	30	_
Has vertical auto keystone correction	Yes	Opicma
Horizontal scan rate	15 ~ 93Khz	
/ertical scan rate	24 ~ 120Hz	
Uniformity	85%	
Screen size	0.47m - 2.84m (18.6in - 111.8in)(Diagonal)	
Lamp info		
Light source	LED	
LED life	30,000 hours	
Optical		
Throw ratio	1.2:1	
Projection distance (m)	0.49m - 2.97m	
Zoom type	Fixed	
Focal length (mm)	12.64	
Native offset	100%	_
Connectivity		-
Connections	Inputs 2 x HDMI, 1 x USB-A wireless	
Connections	Inputs 2 x HDMI, 1 x USB-A wireless Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm	
		_
General	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm	-
General Noise level (typical)	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB	-
General Noise level (typical) PC compatibility	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac	-
General Noise level (typical)	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages:	– nan,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Rom
General Noise level (typical) PC compatibility OSD / display languages	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Chinese	- nan,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Rom
General Noise level (typical) PC compatibility	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplifed),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese	– nan, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Rom
General Noise level (typical) PC compatibility OSD / display languages 24/7 operation Operating conditions	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese Yes	– nan, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Rom
General Noise level (typical) PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m	– nan, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Rom
General Noise level (typical) PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes	– nan,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Rom
General Noise level (typical) PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2	-
General Noise level (typical) PC compatibility DSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual	nan, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Rom
General Noise level (typical) PC compatibility DSD / display languages 24/7 operation Deperating conditions Remote control Speaker count Watts per speaker n the box Deperating system compatibility	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries	-
General Noise level (typical) PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Power	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+	-
General Noise level (typical) PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Power Power Power supply	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+ 100 ~ 240V, 50 ~ 60Hz	-
General Noise level (typical) PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Power Power supply Power consumption	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+	aan, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Rom
General Noise level (typical) PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Power Power consumption (standby)	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, Gerr (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, IOS 8+ 100 ~ 240V, 50 ~ 60Hz 0.5W	aan, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Rom
General Noise level (typical) PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Power Power consumption (standby) Battery life	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+ 100 ~ 240V, 50 ~ 60Hz	an, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Rom
General Noise level (typical) PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Power Power supply Power consumption (standby) Battery life Weight and dimensions	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,Gerr (simplified),Spanish,Swedish,Ohinese (traditional),Turkish,Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+ 100 - 240V, 50 - 60Hz 0.5W Up to 2.5hrs	- nan,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Rom
General Noise level (typical) PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Power Power consumption (standby) Battery life	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm 30dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, Gerr (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, IOS 8+ 100 ~ 240V, 50 ~ 60Hz 0.5W	- nan,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Rom

Copyright © 2018, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 14112018011944