

EH337

High resolution, versatile and powerful



- Bright 1080p projector 3600 ANSI lumens
- Installation flexibility 1.3x zoom
- Easy connectivity 2x HDMI, MHL, USB Power
- Clear, powerful audio 10W speaker

Beam bright, eye catching content with the Full HD 1080p EH336 projector. Perfect for classroom and meeting room presentations, this projector is designed to be used at any time of day.

Additionally, it boasts easy connectivity with multiple inputs including two HDMI, MHL, VGA and a built in 10W speaker. You can even use the USB Power to connect and power HDMI dongles such as the Google Chromecast.

Specifications

Display/image Display technology DIP

Resolution 1080p Full HD (1920x1080)

3,600 lumens Brightness Contrast ratio 20,000:1 16:9 Native aspect ratio Aspect ratio - compatible 4:3 Keystone correction -+/-40°

vertical

Horizontal scan rate 15.38 ~ 91.15Khz Vertical scan rate 50 ~ 85(120 for 3D)Hz

Uniformity 70%

0.69m ~ 7.59m (27" ~ 299") (diagonal) Screen size

Lamp info Light source type Lamp Lamp watts 240

Lamp life (hours) 3500 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)

Optical

1.58:1 - 2.06:1 Throw ratio Projection distance (m) 1.2m - 10.2m 1.3 Zoom Zoom type Manual Focal length (mm) 16.91 ~ 21.6 Native offset 116%

Connectivity

Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1

x Audio 3.5mm

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232

General

Noise level (typical) 27dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 2D compatibility

4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

3D Full 3D

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages 25 languages

A rabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Greek, Hungarian, Greek, Hun(simplified). Spanish. Swedish. Chinese

(traditional), Turkish, Vietnamese

Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

Card style Remote control Speaker count Watts per speaker 10W

In the box AC power cord, remote control, Battery, basic user manual

Power Power supply

100 ~ 240V. 50 ~ 60Hz

Power consumption 0.5W

(standby)

205W Power consumption (min) Power consumption (max) 295W

Weight and dimensions

Net weight 2.91kg Dimensions (W x D x H) 316 x 244 x 108

mm



