

UHD51

True to life detail - 4K Ultra HD projector



- 4K UHD resolution and HDR compatible
- Amazing colour accurate 100% Rec.709 colours, 2400 ANSI lumens
- Fluid viewing PureMotion frame interpolation
- · Easy installation vertical lens shift

Immerse yourself in a world of Ultra HD. The UHD51 delivers the ultimate in home entertainment with impressive 4K cinema quality images. Enjoy excellent colour depth, crystal clear detail, and high contrast for a stunningly immersive experience.

Packed with the latest technology and features, this compact UHD projector boasts High Dynamic Range (HDR) compatibility, HDCP 2.2 support and sophisticated PureMotion frame-interpolation processing which eliminates motion blurring or image judder. An RGBRGB colour wheel provides accurate, true to life colour rendition of 100% Rec.709 - perfect for recreating the big-screen experience at home.

Specifications

PC compatibility

2D compatibility

(mm)

Display/image Display technology DIP Resolution UHD (3840x2160) Brightness 2,400 lumens Contrast ratio 500,000:1 16:9 Native aspect ratio Aspect ratio - compatible 4:3 Horizontal scan rate 31 ~ 135Khz Vertical scan rate 24 ~ 120Hz Uniformity 75% 0.87m - 7.68m (34.1in - 302.4in)(Diagonal) Screen size Lamp info Light source 240 Lamp watts 4000 (Bright), 15000 (Dynamic), 10000 (Eco) Lamp life (hours) Optical Throw ratio 1.21:1 - 1.59:1 Projection distance (m) 1.2m - 8.1m 1.3 Zoom Manual Zoom type Focal length (mm) 12 81 ~ 16 74 Lens shift Vertical +10, % Native offset 105% Connectivity Connections Inputs $2 \times HDMI 2.0$, $1 \times VGA (YPbPr/RGB)$, $1 \times Audio$ Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power $\textbf{Control} \ 1 \ x \ \text{USB-A service,} \ 1 \ x \ \text{RS232,} \ 1 \ x \ \text{RJ45,} \ 1 \ x \ 12V$ triaaer General Noise level (typical) 25dB





1080p(50/60Hz), 2160p(50/60Hz) 3D compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 3D Full 3D Security Security bar, Kensington Lock, Password protected interface OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified).Spanish 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Operating conditions Remote control Backlit home remote Speaker count Watts per speaker 5W In the box Lens cap AC power cord Remote control 2x AAA batteries Basic user manua Power 100 ~ 240V 50 ~ 60Hz Power supply Power consumption 0.5W (standby) Power consumption (min) 249W Power consumption (max) 305W Weight and dimensions Net weight 5.22kg 392 x 281 x 118 Dimensions (W x D x H)

XGA, SVGA, VGA, Mac

UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD,

480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz),