

CHRISTIE HS SERIES D16WU-HS / D16HD-HS

Auditoriums | Enterprise venues and boardrooms | Entertainment venues | Houses of worship
Hotels | Live events and conferences | Rental and staging | Trade shows and exhibitions

Power is freedom

Enjoy the freedom of unrestricted power. Hitting 16,000 lumens, the Christie® D16WU-HS and D16HD-HS are the lightest and brightest 1DLP® laser projectors to operate at full-brightness on a single 15A, 110V circuit. There's no need for high-power runs. Simply plug it into a standard 110V outlet and start the show!

Visuals are stunning thanks to the enhanced color accuracy of Christie's patented BoldColor Technology and HD or WUXGA resolution.

The long-lasting and reliable laser light source and affordability of 1DLP technology means these projectors are a cost-effective option for high-use applications. With built-in Christie Twist™, users have the tools needed to quickly and easily set up and align irregular screens and multi-projector displays.

These projectors come with the option to add Christie Mystique™ automated camera-based alignment software, letting you quickly stage, install, align, and recalibrate multi-projection systems in minutes.



CHRISTIE®

Technical specifications

Christie D16WU-HS

Christie D16HD-HS

Image	brightness (lumens)	• 17,400 ISO • 15,500 ANSI	• 15,750 ISO • 14,000 ANSI	
	color wheel	• 4 segment (RGBY) - 2X or 3X speed		
	contrast (nominal)	• Full on/off (Christie RealBlack enabled): 2,000,000:1 • Dynamic contrast: 5000:1 • Full on/off (Christie RealBlack disabled): 1200:1 • ANSI 250:1		
Display technology	type	• 1 x 0.96" DMD		
	native resolution	• 1920 x 1200 (2,304,000 pixels) 16:10	• 1920 x 1080 (2,073,600 pixels) 16:9	
Illumination	type	• Laser phosphor with Christie BoldColor Technology		
	performance	• 20,000 hrs to 50%		
Signal inputs	standard	• HDMI x 2 (one on rear panel, one on bottom of projector, independently selectable) • 3GSDI x 1 (BNC) • DVI-D x 1 (digital only) • HD15 x 1 • USB x 1 (Type A) • Wi-Fi® dongle (optional) • HDBaseT x 1		
	signals	• HDTV formats VGA through to WUXGA (1920 x 1200) • Horizontal and vertical scaling while maintaining aspect ratio, all inputs		
	3D	• HDMI 1.4, HDBaseT - frame packed, top/bottom, side-by-side (up to 120Hz output) • 3D sync in (BNC) - for genlocking projectors • 3D sync out (BNC) - for genlocking projectors, or controlling emitter or polarizer		
	pixel clock	• 162MHz		
	scan rates	• Horizontal: 15-91kHz • Vertical: 24-85Hz		
	Signal outputs	monitor out (loop-through)	• 3GSDI x 1 (BNC) • HDMI x 1 (HDMI out)	
	Control and networking	• RS-232 in • Control via HDBaseT • Ethernet (10/100) RJ45 • Built-in backlit keypad • Wired remote control (3.5mm stereo) • Loop out available for daisy chaining • 12VDC trigger at 200mA (ID:2.5mm)		
Warping and blending		standard	• Christie Twist	
Lenses	optional	• Christie Twist Premium and Twist Pro • Christie Mystique automated camera-based alignment		
	mount type	• Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses)		
	lens options	• 0.38:1 UST lens • 0.84-1.02:1 zoom lens (no zoom/focus memory) • 1.02-1.36:1 zoom lens (no zoom/focus memory) • 1.2-1.5:1 zoom lens (full ILS) • 1.5-2.0:1 zoom lens (full ILS) • 2.0-4.0:1 zoom lens (full ILS) • 4.0-7.0:1 zoom lens (full ILS)		
	offsets for full ILS lenses	• ±120% Vertical • ±50% Horizontal	• ±140% Vertical • ±50% Horizontal	
	offsets for 0.84-1.02:1	• +111/-43% Vertical • +21/-35% Horizontal	• +108/-74% Vertical • +29/-42% Horizontal	
	offsets for 1.02:1-1.36:1	• +110/-66% Vertical • +32/-46% Horizontal	• +125/-98% Vertical • +40/-49% Horizontal	
Accessories	standard	• IR remote w/wired remote jack (wire not included) • AC line cord for projector head • User manual		
	optional	• Christie One Rigging Frame • Lens adapter for E Series lenses • 1DWUSB-BGN (wireless dongle for video and control) • Christie HS Series fog filter refills (1 set) • Christie HS Series fog filter covers and filters (order once per projector then only filter refills) • Christie One Mount Plus • One Mount Extender Rod • Replacement remote control • One Mount Rigging Kit (used with One Mount, One Mount Plus and/or One Mount Extender Rod)		
Power requirements	operating voltage	• Normal mode: 110-240 VAC @ 50/60Hz		
	power consumption	• Normal mode: 1250W ±15% (220 VAC), 1300W ±15% (110 VAC) • Eco1 mode: 1020W ±15% (220 VAC), 1050W ±15% (110 VAC) • Eco2 mode: 700W ±15% (220 VAC), 700W ±15% (110 VAC)		
	operating current	• Normal mode: 6.0A ±15% (220 VAC), 11.9A ±15% (110 VAC) • Eco1 mode: 4.7A ±15% (220 VAC), 9.6A ±15% (110 VAC) • Eco2 mode: 6.5A ±15% (220 VAC), 3.2A ±15% (110 VAC)		
	dissipation	• Normal mode: 4450 BTU/hr • Eco1 mode: 3600 BTU/hr • Eco2 mode: 2450 BTU/hr		
Audible noise	• Typical: 45dBA • Eco mode: 39dBA			
Physical	size	• (L xWxH) 26.65 x 23.46 x 7.99" (677 x 596 x 203mm) w/o feet		
	shipping size	• (L xWxH) 36.34 x 33.19 x 20.2" (923 x 843 x 513mm)		
	weight (w/o lens)	• 93.7lbs (42.5kg)		
	shipping weight	• 119lbs (54kg)		
Operating environment	temperature	• 32-104°F (0-40°C)		
	humidity	• 0-85% non-condensing		
Regulatory	• Contact Christie for the timing of certifications: UL/CSA/IEC 60950-1, FCC Class A, CE, FDA, CCC, KC, PSE, CU, SABS, BIS, VCCI, RCM, Ukr, TER, SASO • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • RoHS, REACH, WEEE			
Warranty	• Three years parts and labor on the projector • Three years or 15,000 hours parts and labor on the illumination system ¹ • Contact an authorized Christie representative for full details of our limited warranty			

¹ Please reference Christie Standard Limited Warranty document for details.

For the most current specification information, please visit christiedigital.com

Copyright 2019 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4797 May 19



CHRISTIE[®]
Kitchener, Ontario