

UHD380X

Bright 4K UHD smart home projector









- 4K UHD resolution HDR and HLG compatible
- Lights on viewing 3500 ANSI lumens
- Amazing colour accurate Rec.709 colours
- Feature packed TapCast, built-in media player and PureMotion

Immerse yourself in a world of 4K Ultra HD. The UHD380X delivers the ultimate in smart home entertainment with bright 4K UHD images, accurate colours, crystal clear detail, and sparkling contrast.

Packed with the latest technology and a range of features, this compact projector boasts High Dynamic Range (HDR) and HLG compatibility, Full 3D, HDMI 2.0, a built-in media player and PureMotion frame-interpolation processing which eliminates motion blur or image judder.

Specifications

Display/image Display technology DIP Resolution UHD (3840x2160) Brightness 3,500 lumens Contrast ratio 500,000:1 16:9 Native aspect ratio Aspect ratio - compatible 4:3 Horizontal scan rate 31 ~ 135Khz Vertical scan rate 24 ~ 120Hz 75% Uniformity 0.87m ~ 7.68m (34.1" ~ 302.4") diagonal Screen size Lamp info Light source type 240 Lamp watts 4000 (Bright), 15000 (Dynamic), 10000 (Eco) Lamp life hours (up to) Optical Throw ratio 1.21:1 ~ 1.59:1 Projection distance (m) 1.2m - 8.1m Zoom 1.3 Zoom type Manual 12.81 ~ 16.74 Focal length (mm) Lens shift Vertical +10% Native offset Connectivity Connections Inputs 2 x HDMI 2.0, 1 x VGA (YPbPr/RGB), 1 x Audio

Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power

Control 1 x USB-A service, 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x USB-A reader/wireless, 1 x USB-A wireless

General

Noise level (typical) 25dB

UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac PC compatibility

480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) 2D compatibility

Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 3D compatibility

1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

Full 3D 3D

Security bar, Kensington Lock, Password protected interface Security

OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish

Operating conditions $5^{\circ}\text{C} \sim 40^{\circ}\text{C},$ Max. Humidity 85%, Max. Altitude 3000m

Remote control Backlit home remote

Speaker count Watts per speaker 5W In the box Lens cap

AC power cord Remote control 2x AAA batteries Basic user manual

Wireless USB adapter - WUSB

Optional wireless models

Power

100 ~ 240V, 50 ~ 60Hz Power supply

Power consumption 0.5W

(standby)

249W Power consumption (min) Power consumption (max) 305W

Weight and dimensions

Net weight 5.22kg Dimensions (W x D x H) 392 x 281 x 118

mm



