

## X371











- **Bright XGA projector 3800 ANSI lumens**
- Easy connectivity HDMI, VGA, USB power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Project bright and vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the X371 boasts amazing colour, long lamp life and energy-saving features for a lower overall cost of ownership.

This projector is easy to connect to with multiple inputs, a built-in speaker and USB power. Perfect for connecting HDMI dongles such as Google Chromecast or a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings or classes with the optional carry bag (sold separately).



## **Specifications**

Specifications	
Display/image	
Display technology	DLP™
Resolution	XGA (1024x768)
Brightness	3,800 lumens
Contrast ratio	25,000:1
Native aspect ratio	4:3
Aspect ratio - compatible	16:9
Keystone correction -	+/-40°
Horizontal scan rate	45.00 04.451/1-
	15.38 ~ 91.15Khz
/ertical scan rate	50 ~ 85(120 for 3D)Hz
Jniformity	75%
Screen size	0,71m ~ 7,73m (27,78" ~ 304,4") diagonal
amp info	Lavo
ight source type	Lamp
_amp watts	203
amp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical	
Throw ratio	1,94:1 ~ 2,16:1
Projection distance (m)	1m - 12m
2oom	1,1
Zoom type	Manual
ocal length (mm)	21.85 ~ 24
Native offset	115%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB),
	1 x Composite video, 1 x Audio 3.5mm
	Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A
	Control 1 x RS232
	301101 1 1 10202
General	27.17
Noise level (typical)	27dB
Noise level (max)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
BD	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Card style
Speaker count	1
Vatts per speaker	10W
n the box	40
iii tile box	AC power cord Remote control Battery
	Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption standby)	0.5W
	187\\
Power consumption (min)	187W
Power consumption (max)	225W
Weight and dimensions Dimensions (W x D x H)	316 x 244 x 108
mm	2.50 kg

3,58 kg

3,04 kg

Gross weight

Net weight



